



# Whitlock®

PROVIDING SOLUTIONS, NOT JUST EQUIPMENT



HA Small  
Series Dryer

## HA SERIES HOT AIR DRYERS

HA Series Hot Air Dryers feature a single blower that provides heated air to dry non-hygroscopic materials. Set point process temperature control to 300°F (149°C). 60-1500 CFM (102-2548 m<sup>3</sup>/hr) airflow available.

HA Series Hot Air Dryers include one 12-foot length of high temperature flexible dryer hose. HA Series dryers should be used in conjunction with an appropriately-sized drying hopper

### STANDARD FEATURES

- Regenerative blower on 60, 150 and 260 cfm models (100, 250, 450 m<sup>3</sup>/hr)
- Centrifugal blower on 525, 1000, 1250 and 1500 cfm models (900, 1700, 2100, 2550 m<sup>3</sup>/hr)
- NEMA 1, standard 460/3/60 control panel
- Set point process temperature control to 300°F (149°C)
- Built-in high temperature safety
- "Cabinet style" enclosure with casters on 60/150/260/525 cfm models (100, 250, 450, 890 m<sup>3</sup>/hr)
- Electrical non-fused disconnect
- One (1) 12 feet (3.6m) length of high temperature flexible dryer hose with clamps
- Other supply voltages available
- Inlet air filter

### OPTIONAL FEATURES

- Casters
- 208/3/60, 230/3/60, 380/3/50, 415/3/50, or 575/3/60
- Process heater burnout indicator
- Redundant process air safety



## HA SERIES HOT AIR DRYERS

[www.aecininternet.com](http://www.aecininternet.com)



Model	Max Process Airflow, cfm (m <sup>3</sup> /hr)	Hose Con. Dia., in. (mm)	Length, in. (mm)	Width, in. (mm)	Height, in. (mm)	Shipping weight, lbs. (kg)
HA-60	60 (100)	2 (64)	34 (864)	29 (737)	33 (838)	225 (102)
HA-150	150 (250)	2 (64)	46 (1168)	22 (559)	42 (1067)	275 (125)
HA-225	260 (450)	4 (102)	46 (1168)	22 (559)	42 (1067)	300 (136)
HA-450	525 (900)	5 (127)	37 (940)	50 (1270)	87 (2210)	650 (295)
HA-1000	1000 (1700)	6 (152)	74 (1880)	42 (1067)	81 (2057)	1180 (536)
HA-1250	1250 (2100)	8 (203)	74 (1880)	42 (1067)	81 (2057)	1275 (580)
HA-1500	1500 (2550)	8 (203)	55 (1397)	65 (1651)	80 (2032)	1350 (614)



HA Large Series Dryer

[www.aecinternet.com](http://www.aecinternet.com)  
[aecweb@corpemail.com](mailto:aecweb@corpemail.com)

AEC is committed to a continuing program of product improvement. Specifications, appearances and dimensions are subject to change without notice.  
 © 2011 AEC Bulletin WH1-120.5 Printed in USA

## HA SERIES HOT AIR DRYERS



**Global Headquarters:**

**AEC Schaumburg**  
 1100 E. Woodfield Rd #588  
 Schaumburg, IL 60173  
 Tel: +1 847 273 7700  
 Fax: +1 847 273 7804

**AEC New Berlin**  
 2900 S. 160th Street  
 New Berlin, WI 53151  
 Tel: +1 262 641 8610  
 Fax: +1 262 641 8653



**AEC Suzhou**  
 109 Xingpu Road SIP  
 Suzhou, China 215126  
 Tel: +86 512 8717 1919  
 Fax: +86 512 8717 1916



**AEC Warsaw**  
 ul.Dziakowa 115  
 02-234 Warszawa  
 Tel: + 48 22 390 9720  
 Fax: + 48 22 390 9724



**AEC India**  
 Regus, Level 2, Connaught Place  
 Bund Garden Road, Pune 41100,  
 India  
 Tel: +91 20 4014 7575/40147615  
 Fax: +91 93 7115 4045