



Nomad™ PD-3 Level C

STANDARD FEATURES

- Integrated control interface provides status of drying and conveying functions. Also allows simple start-up, shutdown, and change of drying and conveying parameters
- "Off-the-shelf" programmable controller controls drying and conveying functions
- PID temperature controller provides LED readout of set point and actual process temperature
- Digital dewpoint indicator displays "actual dewpoint" and "high dewpoint" alarm settings
- Sight glass material receiver for minimal inventory on the process machine
- Insulated drying hopper with sight glass and slide gate. Large cleanout door on hoppers
- Single power connection point with electrical disconnect on control cabinet
- SD6.0 and SD9.0 drying hoppers are stainless steel
- SD12, SD17, and SD23 are carbon steel drying hoppers

NOMAD PORTABLE DRYING

Nomad™ portable drying systems provide complete drying and conveying in one compact, portable package. These units automatically convey on demand while providing closed loop drying.





Model	Dryer Process Air Flow		Amp Draw	Voltage	Insulated Drying Hopper Size			
	cfm	m3/hr			cu. ft.	liters	lbs.	kg
PD-2A	90	150	24	460/3/60	6.0	170	200	90
PD-2C	90	150	24		9.0	250	300	135
PD-2B	90	150	24		12.0	340	400	181
PD-3	100	170	27		12.0	340	400	181
PD-4A	150	250	38		12.0	340	400	181
PD-4B	150	250	38		17.0	480	600	272
PD-4C	225	380	48		23.0	650	800	363

NOMAD™ SERIES CONTROL (DUAL BLOWER DRYER MODEL SHOWN)

- “Off-the-shelf” PLC control of drying and conveying functions
- Independent operation of dryer and conveying control circuits
- 1/16 DIN temperature controller with LED readout of process air actual and set point temperature
- Digital dewpoint indication with customer-adjustable high dewpoint alarm set point and LED readout of actual process dewpoint
- Indicator lights and display provide status of desiccant bed regeneration heaters, process and regeneration blowers, and material loading system
- Alarm indication includes: high temperature process air, high temperature regeneration air, and high dewpoint (dirty filter alarm optional)
- Switch on dewpoint demand
- Dryer process auto shutdown sequence

Level A Machine Loading Only	All features listed above plus: <ul style="list-style-type: none"> • Machine loader convey station control • Closed-loop dry air conveying to process • SRI Series stainless steel sight glass receiver
Level B Drying Hopper Loading Only	All features listed above, with the following modifications: <ul style="list-style-type: none"> • Drying hopper loader fills the drying hopper in lieu of machine loader • Includes SRC02 material receiver with hose and pickup wand 1.5" (38mm) FCO open loop standard take-off on discharge of drying hopper
Level C Machine Loading and Dryer Hopper Loading	All features listed above, including both machine loader and drying hopper loader plus: <ul style="list-style-type: none"> • Machine loader convey station with closed loop dry air convey and SRI sight glass vacuum receiver • Drying hopper loader with SRC02 material vacuum receiver and 1.5" (38mm) OD pickup wand with hose

www.aecinternet.com
aecweb@corpemail.com

AEC is committed to a continuing program of product improvement. Specifications, appearances and dimensions are subject to change without notice.
 © 2011 AEC Bulletin WH1-135C.4 Printed in USA



NOMAD PD PORTABLE DRYING SYSTEM



Global Headquarters:

AEC Schaumburg
 1100 E. Woodfield Rd #588
 Schaumburg, IL 60173
 Tel: +1 847 273 7700
 Fax: +1 847 273 7804

AEC New Berlin
 2900 S. 160th Street
 New Berlin, WI 53151
 Tel: +1 262 641 8610
 Fax: +1 262 641 8653



AEC Suzhou
 109 Xingpu Road SIP
 Suzhou, China 215126
 Tel: +86 512 8717 1919
 Fax: +86 512 8717 1916



AEC Warsaw
 ul.Dziakowa 115
 02-234 Warszawa
 Tel: + 48 22 390 9720
 Fax: + 48 22 390 9724



AEC India
 Regus, Level 2, Connaught Place
 Bund Garden Road, Pune 41100,
 India
 Tel: +91 20 4014 7575/40147615
 Fax: +91 93 7115 4045