


RPV SERIES

Remote Proportioning Valve

Technical Specifications

VacTrac™ RPV Remote Proportioning provides reliable proportioning from 0 to 100% of two materials (typically virgin and regrind). A convenient window provides immediate inspection. Quick-release top enables fast, easy cleanout for material changes. 45 degree angled design decreases flex hose wear for less maintenance.



Features

Standard Features

- Corrosion resistant Aluminum construction
- Air operated
- 24VDC or 110 VAC operation
- Dual Solenoid operation (except 3")
- Material Viewing window
- Quick release lid for east cleaning
- Lanyard attached to lid to prevent loss
- 2x aluminum pickup wands
- 2x 10' vinyl flex hoses, four hose clamps
- Central Vacuum System or Hopper Loader compatibility
- O-ring coupler, and a controller assembly with quick-connect cable assembly
- Line sizes available:
 - 1.5"
 - 2.0"
 - 2.5"
 - 3.0"

Optional Features

- Hopper-mount, wall-mount, or floor stand
- Spare controller assembly
- Single Solenoid operation
- Consult factory for other line sizes or voltages

Specifications

Voltage Configuration	Supply Voltage	Control Voltage
B24	115/1/50-60	24 VDC
B115		115/1/50-60
E24	24 VDC	24 VDC